

## N Moxi Now Pro, N Moxi Now 800, N Moxi Now 700 10A receiver in canal (RIC) hearing aid series



Moxi Now

### Performance profile

	Moxi Now Pro	Moxi Now 800	Moxi Now 700
Channels	20	20	16

### Signature features

SpeechZone 2	SpeechZone 2	SpeechZone	
Binaural spatial processing	•	•	
SoundNav	7 environments	6 environments	5 environments
Sound Conductor	•	•	•
MyMusic	Automatic binaural	Automatic binaural	•
Binaural Phone	•	•	•
Automatic Adaptation Manager	•	•	•

### Features

Adaptive directional	Multiband	Multiband	Multiband
Pinna Effect	•	•	•
Frequency compression	•	•	•
AntiShock	•	•	•

### In all technology levels

Natural Sound Balance, data logging and Log It All, feedback manager, wind control, tinnitus masker, manual programs, streaming programs, IntelliVent technology for custom ear pieces, plasma coating, IP67


### Accessories (optional)

Remote control 2, uStream, uDirect 3, uTV 3, uMic


### Receiver type

	Standard (xS)	Power (xP)
Output / gain	114/46	127/57
Open dome	•	•
Closed dome	•	•
Power dome	•	•
Sleeve mold	•	•
cShell	•	•

### Fitting guides






Standard receiver (xS)






Power receiver (xP)

- Open dome
- ... Closed dome
- Power dome or sleeve mold

## ANSI 3.22 2014/IEC 60118-7 2005 2cc coupler technical data

	Reference test frequency - IEC 60118-7 (kHz)	1.6	1.6
	<b>OSPL90</b>		
	Maximum (dB SPL)	114	127
	Nominal (dB SPL)	111	124
	HFA - OSPL90 (dB SPL)	106	120
	at RTF (dB SPL)	105	121
	<b>Full on gain (input 50 dB SPL)</b>		
	Maximum (dB)	46	57
	HFA - FOG (dB)	40	52
	at RTF (dB)	39	52
	<b>Reference test setting (RTS)</b>		
	Frequency range (Hz)	<100 - 8500	<100 - 7300
	Reference test gain (dB)	29	43
	Current drain at RTS (mA)	1.15	1.25
	Typical battery life (h)	90	80
	Equivalent input noise at RTS (dB SPL)	19	18
	Total harmonic distortion at 500 Hz/800 Hz/1600 Hz (%)	1.0/1.0/1.0	1.5/1.0/0.5
<b>Electromagnetic compatibility</b>			
EMC immunity by ANSI c63.19-2011 EMC, omni		M4	M4

## IEC 60118-o OES coupler technical data

	Reference test frequency - IEC 60118-o (kHz)	1.6	1.6
	<b>OSPL90</b>		
	Maximum (dB SPL)	122	133
	at RTF (dB SPL)	114	130
	<b>Full on gain (input 50 dB SPL)</b>		
	Maximum (dB)	58	67
	at RTF (dB)	48	62
	<b>Basic frequency response</b>		
	Frequency range (DIN 45605) (Hz)	<100 - 10000	<100 - 8000
	Reference test gain (dB)	39	55
	Current drain at RTG (mA)	1.15	1.2
	Typical battery life (h)	90	80
	Equivalent input noise at RTG (dB SPL)	19	19
	Total harmonic distortion at 500 Hz/800 Hz/1600 Hz (%)	1.0/1.5/1.5	1.5/1.5/1.0
<b>Electromagnetic compatibility</b>			
EMC immunity by IEC 60118-13, 2011 field strength 90/50/35 V/m, omni. IRIL low/medium/high band (dB SPL)		26/24/25	14/16/19

## Legend

- xS receiver
- xP receiver

## Test conditions

Battery size: 10; Source: voltage 1.3 V

The measurements obtained with a closed configuration using an HA-1 coupler (ANSI-3.7-1995) or occluded ear simulator (EN 60711, coupling arrangement according to fig. 4 in the test standard). The hearing instrument set to Unitron Truefit test settings. LLE is applied at an approximate level of 35 dB SPL. Domes should never be fit on patients with perforated eardrums, exposed middle ear cavities, or surgically altered ear canals. In the case of such a condition, we recommend use of a customized earmold. Sound pressure level of these hearing aids exceeds 132 dB SPL.

We reserve the right to change specification data without notice as improvements are introduced.